

EGL6082



Features

- Support 2 x Full HD Displays
- AMD G Series Quad Core up to 2.4GHz
- Integrated AMD GPU HD8000 series
- 2 x DDR3 SO-DIMM, up to 16GB
- 2 x DP + 1x VGA
- 1 x SATA with Pin 7 VCC + SmartBay®
- Modular I/O design
- Long lifetime support to 2024

System

CPU	AMD G series Quad Core up to 2.4GHz
Graphic	Integrated AMD GPU HD8000 series
Main Memory	2 x DDR3-1600 SO-DIMM socket max. up to 16GB
Storage	1 x SATA in Smartbay® 1 x SATAII standard SATA connector with pin7 power

I/O

Display	2 x Display Port (Full HD)
Audio	2 x 3.5mm Audio Jack
USB	4 x USB 2.0
Serial	4 x RS232C, 1 x UART/RS232/ccTALK, 1 x RS485/ccTALK
LAN	2 x RJ45 Realtek RTL8111G support 10/100/1000Mbps
VGA	1 x VGA
QIO	1 x QIO

Environment & Mechanical

Power Input	+12V DC / 3.5A
Temperature Operation	0°C to +60°C

Certification & Optional OS Installation

OS	Windows 7(E) 64 bit Windows 10(E) 64 bit Linux Ubuntu 16.04 LTS 64 bit
----	--

Security

/	Infineon TPM Chip RootSecure® Entry (option)
---	---

Headquarter

10F-3, No.270, Sec.4,
Chung Hsiao E. Rd.,
Taipei, 10694, Taiwan

T +886 2 2751-7192
E-mail: info@efco.com.tw

EMEA

T +49-991-2009298-0
E-mail: info@efcotec.com

America

T +1-760-827-8600
E-mail: sales-us@efcotec.com



Note : All product specifications are subject to change without notice

EGL6082

Model	Description
EGL6082-2	<ul style="list-style-type: none">• AMD GX-218GL 1.8GHz Dual Core, 1MB L2 cache• 2 x DDR3 SO-DIMM, up to 16GB• SmartBay Supports CFAST, CF, 2.5"/1.8" SSD, SATA DOM and USB drive with key lock option
EGL6082-4	<ul style="list-style-type: none">• AMD GX-420CA 2GHz Quad Core, 2MB L2 cache• 2 x DDR3 SO-DIMM, up to 16GB• SmartBay Supports CFAST, CF, 2.5"/1.8" SSD, SATA DOM and USB drive with key lock option

Headquarter

10F-3, No. 270, Sec. 4,
Chung Hsiao E. Rd.,
Taipei, 10694, Taiwan

T +886 2 2751-7192
E-mail: info@efco.com.tw

EMEA

T +49-991-2009298-0
E-mail: info@efcotec.com

America

T +1-760-827-8600
E-mail: sales-us@efcotec.com



Note : All product specifications are subject to change without notice