

TPM-I15M



Industrial Touch Monitor/Display

Features

- Optimal display resolution 1024 * 768
- VESA 75 * 75 mm wall mount standard
- Durable and sturdy base design
- Optional: 3 tracks Magnetic Strip Reader (MSR)
- Optional: varieties of 2nd displays (8", 10.4"...)
- Adjustable viewing angel freely up to 90° horizontally
- Low power consumption only 20W with LED backlight

I/O

Power Consumption	20W
Input Video Format	VGA/DVI
Input Video signal connector	D-Sub 15 pins + DVI-D
Input Frequency	Horizontal: 31.5 kHz~60.2 kHz

Environment & Mechanical

Power Supply	DC 12V +/- 10%
Temperature Operation	0°C ~55°C
Temperature Storage	-20°C ~65°C
Humidity Operation	10%~90%
Humidity Storage	10%~90%
Weight (net/gross)	3.5kg(net), 4.6kg(net)-with stand
Mounting	Wall Mount, VESA 75 * 75 mm

Certification & Optional OS Installation

OS	CE, FCC
----	---------

LCD

Display	15.0"
Contrast	700:1
Viewing Angle (H/V)	170 degrees (H) , 160 degrees (V)
Response Time	8 ms (typ.)
Brightness	350 cd/m ² (typ.)

Headquarter

10F-3, No.270, Sec.4,
Chung Hsiao E. Rd.,
Taipei, 10694, Taiwan

T +886 2 2751-7192
E-mail: info@efco.com.tw

EMEA

T +49-991-2009298-0
E-mail: info@efcotec.com

America

T +1-760-827-8600
E-mail: sales-us@efcotec.com

EFCO
EverFine Group

Note : All product specifications are subject to change without notice

TPM-I15M

Cabinet Color	Black
Active Area	304 * 228 mm
Optimal Resolution	1024 * 768
Color Arrangement	RGB-stripe

Headquarter

10F-3, No.270, Sec.4,
Chung Hsiao E, Rd.,
Taipei, 10694, Taiwan

T +886 2 2751-7192
E-mail: info@efco.com.tw

EMEA

T +49-991-2009298-0
E-mail: info@efcotec.com

America

T +1-760-827-8600
E-mail: sales-us@efcotec.com



Note : All product specifications are subject to change without notice

TPM-I15M

Model	Description
TPM-I15M	15" Industrial Touch Monitor, D-Sub 15 pins + DVI-D, DC 12V, VESA mount

Headquarter

10F-3, No. 270, Sec. 4,
Chung Hsiao E. Rd.,
Taipei, 10694, Taiwan

T +886 2 2751-7192
E-mail: info@efco.com.tw

EMEA

T +49-991-2009298-0
E-mail: info@efcotec.com

America

T +1-760-827-8600
E-mail: sales-us@efcotec.com



Note : All product specifications are subject to change without notice